

conMIG 400 | conMIG 445 | conMIG 545



2

conMIG 400 | 445 | 545




**TECHNISCHE DATEN TECHNICAL DATA DATOS TÉCNICOS FICHE TECHNIQUE DATI TECNICI TECHNISCHE GEGEVENS DANE TECHNICZNE DADOS TÉCNICOS DATE TEHNICE ТЕХНИЧЕСКИЕ ДАННЫЕ ТЕКНИК БИЛГИЛЕР**

		conMIG 400	conMIG 445	conMIG 545
	50 Hz 60 Hz	400 V	400 V	400 V
		25 A	32 A	50 A
		22 kVA	25 kVA	36 kVA
		0,8	0,8	0,8
		50 - 400 A	50 - 450 A	50 - 550 A
		16 - 34 V	16 - 36 V	16 - 41,5 V
		20 - 52 V	20 - 57 V	20 - 66 V
		2	3	3
		12	12	12
	40 °C	60% 400 A / 34 V 100% 350 A / 31,5 V	60% 450 A / 36,5 V 100% 400 A / 34 V	60% 550 A / 41,5 V 100% 420 A / 35 V
		23	23	23
		H (180°C)	H (180°C)	H (180°C)
		F	F	F
	gas water	206 kg 214 kg	258 kg 266 kg	250 kg 258 kg
		1070x490x1370 1070x490x945	1100x500x1420 1100x500x1000	1100x500x1420 1100x500x1000
	gas water	844.400.001 844.400.002	844.445.005 844.445.001	844.545.005 844.545.001

2

